



2.4x7mm, RoHS Compliant & Pb-Free MICROFUSE (VERY QUICK-ACTING)

TECHNICAL PARAMETERS/ :

PART NO. 目录编号	CURRENT RATING 额定电流	SAFETY APPROVALS 安全认证							REFERENCE (A ² .Sec.) (RoHS) iT 参考值	
		CCC		UL(cUL)		UR(cUR)		CSA		PSE
		L	H	L	H	L	H	L		L
20N-0160H/L	160mA		●	●		●	●		0.002313	
20N-0200H/L	200mA		●	●		●	●		0.002719	
20N-0250H/L	250mA	●		●	●		●	●	0.005643	
20N-0300H/L	300mA		●	●		●	●		0.008507	
20N-0315H/L	315mA	●		●	●		●	●	0.009699	
20N-0375H/L	375mA		●	●		●	●		0.01937	
20N-0400H/L	400mA	●	●	●			●	●	0.01841	
20N-0500H/L	500mA	●		●	●		●	●	0.03792	
20N-0600H/L	600mA		●	●			●	●	0.03965	
20N-0630H/L	630mA	●	●	●			●	●	0.04021	
20N-0700H/L	700mA		●	●			●	●	0.07328	
20N-0750H/L	750mA		●	●			●	●	0.08122	
20N-0800H/L	800mA	●	●	●			●	●	0.1002	
20N-010H/L	1A	●	●	●			●	●	0.4457	
20N-012H/L	1.2A		●	●			●	●	0.2627	
20N-013H/L	1.25A	●	●	●			●	●	0.3341	
20N-015H/L	1.5A		●	●			●	●	0.5409	
20N-016H/L	1.6A	●	●	●			●	●	0.5568	
20N-020H/L	2A	●	●	●			●	●	1.038	
20N-023H/L	2.25A		●	●			●	●	1.076	
20N-025H/L	2.5A	●	●	●			●	●	1.899	
20N-030H/L	3A		●	●			●	●	2.851	
20N-032H/L	3.15A	●			●	●	●	●	2.049	
20N-035H/L	3.5A				●	●	●	●	2.704	
20N-040H/L	4A	●			●	●	●	●	3.666	
20N-050H/L	5A	●			●	●	●	●	6.102	
20N-060H/L	6A		●	●	●	●	●	●	6.802	
20N-063H/L	6.3A				●	●	●	●	8.075	
20N-070H/L	7A				●	●	●	●	10.18	
20N-080H/L	8A				●	●	●	●	16.21	
20N-090H/L	9A				●	●	●	●	18.77	
20N-100H/L	10A				●	●	●	●	25.54	
20N-120H/L	12A						●	●	50.89	
20N-150H/L	15A						●	●	68.28	
20N-200H/L	20A						●		147.1	

DENOTES FOR APPROVED

H DENOTES FOR 250V	H	250V
L DENOTES FOR 125V	L	125V 100mA-10A
L DENOTES FOR 72V	L	72V 12A-15A
L DENOTES FOR 60V	L	60V 20A

INTERRUPTING CAPACITY /

50 amperes at 125V AC (100mA-3A) , 50 amperes at 250V AC (375mA-3A)
 30 amperes at 125V AC (3.15A-10A)
 30 amperes at 250V AC (100mA-350mA, 3.15A-10A)
 30 amperes at 72V AC (12A-15A), 50 amperes at 60V DC (20A)
 100 amperes at 125V AC (1A-5A) PSE, 50 amperes at 125V DC (250mA-5A) CCC
 50 amperes at 125V DC (100mA-3A) UL/cUL, 50 amperes at 125V DC (3.15A-10A) UR/cUR

Dimensions/ :

Standards/	UL 248-1, UL 248-14	
Operating Temperature/	-55	-125
Storing Temperature/	-55	-85
Resistance to soldering heat/	260	10s Max.
Solderability/	245 ± 5 , 5s± 0.5s	

20N AVERAGE I-T CHARACTERISTICS CURVE (FOR REFERENCE ONLY)

20N I-T ()

TIME(s)/ 时间(秒)

PACKING/

1. INNER BOX/ : AMMO PACK

2. OUTER CARTON/ : 10 INNER BOXES / CARTON
 CARTON SIZE / L440x W270x H230(mm)

CURRENT(A)/ 电流(安培)