Ⓗ 25S

Φ3.6x10mm, RoHS Compliant & Pb-Free
SLOW-BLOW MICROFUSE

PATENT NO. **ZL 201320197259.0 ZL 201120540121.7**

INTERRUPTING CAPACITY /

50 amperes at 125V/250V AC
35 amperes at 250V AC CCC
70 amperes at 265V AC (In practice)
110 amperes at 220V AC (In practice)

Dimensions/ :

TECHNICAL PARAMETERS/ :

PART NO. 目录编号	CURRENT RATING 额定电流	SAFETY APPROVALS 安全认证								REFERENCE (A^2.Sec.) (RoHS) I^2T 参考值
		CCC	TÜV		UR(cUR)		PSE		KC	
		H	H	L	H	L	H	L	H	
25S-010H/L	1A	●	●	●	●	●	●	●		1.502
25S-012H/L	1.2A		●	●	●	●	●	●		2.592
25S-013H/L	1.25A	●	●	●	●	●	●	●	●	3.000
25S-015H/L	1.5A		●	●	●	●	●	●		4.225
25S-016H/L	1.6A	●	●	●	●	●	●	●	●	4.872
25S-020H/L	2A	●	●	●	●	●	●	●	●	10.15

● DENOTES FOR APPROVED **●**
H DENOTES FOR 250V **H 250V**
L DENOTES FOR 125V **L 125V**

Standards/ **UL 248-1, UL 248-14, IEC 60127-1 IEC 60127-7**
Operating Temperature/ **-55 ~125**
Storaging Temperature/ **-55 ~85**
Resistance to soldering heat/ **260 10s Max.**
Solderability/ **245 ± 5 , 5s ± 0.5s**

25S AVERAGE I-T CHARACTERISTICS CURVE
(FOR REFERENCE ONLY)
25S I-T ( )

ELECTRICAL CHARACTERISTICS/ :

% of CURRENT RATING 额定电流的 %	BLOWING TIME 熔断时间	
100%	4 hours Min.	最快 4 小时
200%	60 seconds Max.	最慢 60 秒

TIME(s)/ 时间 (秒)

CURRENT(A)/ 电流 (安培)

PACKING/

1. INNER BOX/ : AMMO PACK



2. OUTER CARTON/ : 10 INNER BOXES / CARTON
CARTON SIZE / L440x W315 x H255(mm)