

Φ3.6x10mm, RoHS Compliant & Pb-Free  
GLASS TUBE MICROFUSE (FAST-BLOW)

**TECHNICAL PARAMETERS/**

PART NO. 目录编号	CURRENT RATING 额定电流	SAFETY APPROVALS 安全认证					REFERENCE (A <sup>2</sup> .Sec.) (RoHS) I <sup>2</sup> T 参考值
		UL		cUL		CSA	
		H	L	H	L	L	
31NM,32NM-0300H/L	300mA	●	●	●	●	●	0.07196
31NM,32NM-0315H/L	315mA	●	●	●	●	●	0.08236
31NM,32NM-0350H/L	350mA	●	●	●	●	●	0.09546
31NM,32NM-0375H/L	375mA	●	●	●	●	●	0.1172
31NM,32NM-0400H/L	400mA	●	●	●	●	●	0.1389
31NM,32NM-0500H/L	500mA	●	●	●	●	●	0.09975
31NM,32NM-0600H/L	600mA	●	●	●	●	●	0.1354
31NM,32NM-0630H/L	630mA	●	●	●	●	●	0.1422
31NM,32NM-0750H/L	750mA	●	●	●	●	●	0.1956
31NM,32NM-0800H/L	800mA	●	●	●	●	●	0.2463
31NM,32NM-010H/L	1A	●	●	●	●	●	0.3606
31NM,32NM-012H/L	1.2A	●	●	●	●	●	0.5181
31NM,32NM-013H/L	1.25A	●	●	●	●	●	0.5728
31NM,32NM-015H/L	1.5A	●	●	●	●	●	0.8601
31NM,32NM-016H/L	1.6A	●	●	●	●	●	1.115
31NM,32NM-020H/L	2A	●	●	●	●		2.189
31NM,32NM-023H/L	2.25A	●	●	●	●		2.463
31NM,32NM-025H/L	2.5A	●	●	●	●		1.911
31NM,32NM-030H/L	3A	●	●	●	●		3.420
31NM,32NM-032H/L	3.15A	●	●	●	●		3.833
31NM,32NM-035H/L	3.5A	●	●	●	●	●	3A

N

Standards/ UL 248-1, UL 248-14  
 Operating Temperature/ -55 ~125  
 Storing Temperature/ -55 ~85  
 Resistance to soldering heat/ 260 10s Max.  
 Solderability/ 245 ± 5 , 5s± 0.5s