

Φ4.5x15mm, RoHS Compliant & Pb-Free
GLASS TUBE FUSE (FAST-BLOW)

TECHNICAL PARAMETERS/

PART NO. 目录编号	CURRENT RATING 额定电流	SAFETY APPROVALS 安全认证						REFERENCE (A ² .Sec.) (RoHS) iT 参考值
		UR/cUR			PSE		KC	
		H ₁	H ₂	L	H ₂	L	H ₂	
41NM,42NM-0300H ₁ /H ₂ /L	300mA	●	●	●			●	0.0293
41NM,42NM-0315H ₁ /H ₂ /L	315mA	●	●	●			●	0.0335
41NM,42NM-0350H ₁ /H ₂ /L	350mA	●	●	●			●	0.040
41NM,42NM-0375H ₁ /H ₂ /L	375mA	●	●	●			●	0.044
41NM,42NM-0400H ₁ /H ₂ /L	400mA	●	●	●			●	0.060
41NM,42NM-0500H ₁ /H ₂ /L	500mA	●	●	●			●	0.109
41NM,42NM-0600H ₁ /H ₂ /L	600mA	●	●	●			●	0.167
41NM,42NM-0630H ₁ /H ₂ /L	630mA	●	●	●			●	0.174
41NM,42NM-0750H ₁ /H ₂ /L	750mA	●	●	●			●	0.275
41NM,42NM-0800H ₁ /H ₂ /L	800mA	●	●	●			●	0.284
41NM,42NM-010H ₁ /H ₂ /L	1A	●	●	●	●	●	●	0.525
41NM,42NM-012H ₁ /H ₂ /L	1.2A	●	●	●	●	●	●	0.604
41NM,42NM-013H ₁ /H ₂ /L	1.25A	●	●	●	●	●	●	0.626
41NM,42NM-015H ₁ /H ₂ /L	1.5A	●	●	●	●	●	●	1.426
41NM,42NM-016H ₁ /H ₂ /L	1.6A	●	●	●	●	●	●	1.500
41NM,42NM-020H ₁ /H ₂ /L	2A	●	●	●	●	●	●	3.436

Standards/ UL 248-1, UL 248-14
 Operating Temperature/ -55 ~125
 Storing Temperature/ -55 ~85
 Resistance to soldering heat/ 260 10s Max
 Solderability/ 245 ± 5 , 5s± 0.5s