

5.2x20mm, RoHS Compliant & Pb-Free
GLASS TUBE FUSE (MEDIUM SLOW-BLOW)

TECHNICAL PARAMETER

PART NO. 目录编号	CURRENT RATING 额定电流	DIFFERENCE (%) 差值
51MS,52MS-0100H/L	100mA	27
51MS,52MS-0125H/L	125mA	30
51MS,52MS-0150H/L	150mA	25
51MS,52MS-0160H/L	160mA	15
51MS,52MS-0200H/L	200mA	63
51MS,52MS-0250H/L	250mA	1
51MS,52MS-0300H/L	300mA	7
51MS,52MS-0315H/L	315mA	3
51MS,52MS-0350H/L	350mA	1
51MS,52MS-0375H/L	375mA	7
51MS,52MS-0400H/L	400mA	6
51MS,52MS-0500H/L	500mA	4
51MS,52MS-0600H/L	600mA	2
51MS,52MS-0630H/L	630mA	0
51MS,52MS-0750H/L	750mA	1

- Standards/ 500mA 0.6880 **UL 248-1, UL 248-14**
- Operating Temperature/ **-55 ~125**
- Storing Temperature/ **-55 ~85**
- Resistance to soldering heat/ **260 10s Max**
- Solderability/ **245 ± 5 , 5s± 0.5s**