



Φ6.35x32mm, RoHS Compliant & Pb-free  
CERAMIC TUBE FUSE (FAST-BLOW)

**INTERRUPTING CAPACITY /**

- 10,000 amperes at 125V AC (500mA-15A)
- 35 amperes at 250V AC (500mA-1A)
- 100 amperes at 250V AC (1.2A-3.5A)
- 200 amperes at 250V AC (4A-10A)
- 750 amperes at 250V AC (12A-15A)
- 100 amperes at 125V AC (20A-30A)
- 100 amperes at 250V AC (20A-30A)
- 1000 amperes at 300V AC (20A-30A) UR/cUR
- 1000 amperes at 300V AC (0.5A-15A) UL/cUL
- 500 amperes at 125V AC (1A-15A) PSE
- 100 amperes at 250V AC (1A-30A) PSE
- 100 amperes at 250V AC (300mA-3A) KC
- 100 amperes at 250V AC (4A-10A) KC
- 10,000 amperes at 125V DC (2.5A-15A) UL/cUL
- 400 amperes at 125V DC (20A-30A) UR/cUR

**Dimensions/ :**

**65NM AVERAGE I-T CHARACTERISTICS CURVE**  
(FOR REFERENCE ONLY)

**65NM I-T ( )**

TIME(S)/时间(秒)

**ELECTRICAL CHARACTERISTICS/ :**

% of CURRENT RATING 额定电流的 %	BLOWING TIME 熔断时间	
100%	4 hours Min.	最快 4 小时
135%	1 hour Max.	最慢 1 小时
200%	120 seconds Max.	最慢 120 秒

- Standards/** UL 248-1, UL 248-14
- Operating Temperature/** -55 ~-125
- Storing Temperature/** -55 ~-85
- Resistance to soldering heat/** 260 10s Max.
- Solderability/** 245 ± 5 , 5s± 0.5s

CURRENT(A)/ 电流 (安培)