

HC10NM 20A-50A (空调专用)

Class of operation: gR

保护特性: gR

Standard/ IEC 60269-4, GB/T 13539.4, UL 248-13

INTERRUPTING CAPACITY /

50,000 A at 500V AC (IEC)

50,000 A at 400V AC (UL)

10,000 A at 250V AC

Dimensions/ :

Unit 单位: mm

TECHNICAL PARAMETERS/ :

PART NO. 目录编号	CURRENT RATING 额定电流	SAFETY APPROVALS 安全认证		
		CCC	TUV	cURus
10NM20	20A	●	●	●
10NM25	25A	●	●	●
10NM30	30A	●	●	●
10NM32	32A	●	●	●
10NM35	35A	●	●	●
10NM40	40A	●	●	●
10NM50	50A	○		

HC10NM 平均 I-T 曲线图 (仅供参考)

AVERAGE I-T CHARACTERISTICS CURVE
(FOR REFERENCE ONLY)

ELECTRICAL CHARACTERISTICS/ :

% of CURRENT RATING 额定电流的 %	BLOWING TIME 熔断时间	
113%	1 hour Min.	最快 1 小时
160%	1 hour Max.	最慢 1 小时

TIME(s)/ 时间 (秒)

CURRENT(A)/ 电流 (安培)